

DISTRIBUTION

Model:ATS3200



Switchboard Data

		50Hz	60Hz		
VOLTAGE	VOLTS	231/400		COLOUR	BS4800 16E53
MAIN BUS BAR RATING	AMPS	3200		MAXIMUM OPERATING AMBIENT	35°C
FORM RATING	Form Type	TBA		DIMENSIONS (mm)	DEPTH WIDTH HEIGHT
IP RATING	IP	65			920 2260 2520
SWITCHBOARD kA RATING	kA	50kA		WEIGHT (kg) with crash frame	1840
NUMBER OF POLES	Incomers Feeders	4		LIFTING ARRANGEMENTS:	
CABLE ENTRIES:			FORK POCKETS		
Incomer 1 (mains)		Bottom		Fork Pockets	✓
Incomer 2 (Generator)		Bottom		Single Point Lift/Hole Diameter	x
				2 x Top Lifting Eyes/Hole Diameter	✓
				4 x Top Lifting Eyes/Hole Diameter	x

Unit B1 Colliery Business Park
Pike Road, Eythorne, Kent
CT15 4FE

t 01304 833900
e rental@powerhire.uk.com
www.powerhire.uk.com



SWITCHGEAR

Model:ATS3200

ATS Switchgear Details

BREAKER	MANUFACTURER	RATING		CONNECTION METHOD	
Incomer 1 (Mains)		Current	3,200 Amps	Phases	M12 Bolt - Up to 6 load cables per phase
		Fault kA	65kA	Neutral	M12 Bolt - Up to 6 load cables
		# Poles	4	Earth	M10 Bolt - Earth Bar external to panel
		Notes:			
	Model SACE E3N 32 Trip Type PR121/P				
Incomer 2 (Generator)		Current	3,200 Amps	Phases	M12 Bolt - Up to 6 load cables per phase
		Fault kA	65kA	Neutral	M12 Bolt - Up to 6 load cables
		# Poles	4	Earth	M10 Bolt - Earth Bar external to panel
		Notes:			
	Model SACE E3N 32 Trip Type PR121/P				

CONTROL SYSTEM

Model	DSE 332
Control Functions:	
Generator Start Signal	✓
Auto Utility Return	✓
Manual Utility Return	✓
Utility Paralleling	x
Output devices	QTY

